



P-Channel MOSFET

AO4407A (KO4407A)

■ Features

- $V_{DS} (V) = -30V$
- $I_D = -12 A (V_{GS} = -20V)$
- $R_{DS(ON)} < 11m\Omega (V_{GS} = -20V)$
- $R_{DS(ON)} < 13m\Omega (V_{GS} = -10V)$
- $R_{DS(ON)} < 17m\Omega (V_{GS} = -6V)$



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	V_{DS}	-30	V	
Gate-Source Voltage	V_{GS}	± 25		
Continuous Drain Current	I_D	$T_A = 25^\circ C$	-12	A
		$T_A = 70^\circ C$	-10	
Pulsed Drain Current	I_{DM}	-60		
Avalanche Current	I_{AR}	-26		
Avalanche energy	$L = 0.3mH$	E_{AR}	101	mJ
Power Dissipation	P_D	$T_A = 25^\circ C$	3.1	W
		$T_A = 70^\circ C$	2	
Thermal Resistance.Junction- to-Ambient	R_{thJA}	$t \leq 10s$	40	$^\circ C/W$
		Steady-State	75	
Thermal Resistance.Junction- to-Lead	R_{thJL}	24		
Junction Temperature	T_J	150	$^\circ C$	
Storage Temperature Range	T_{stg}	-55 to 150		

P-Channel MOSFET

AO4407A (KO4407A)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =-250 μA, V _{GS} =0V	-30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V			-1	μA
		V _{DS} =-30V, V _{GS} =0V, T _J =55°C			-5	
Gate-Body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±25V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} I _D =-250 μA	-1.7		-3	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =-20V, I _D =-12A			11	mΩ
		V _{GS} =-20V, I _D =-12A T _J =125°C			15	
		V _{GS} =-10V, I _D =-12A			13	
		V _{GS} =-6V, I _D =-10A			17	
On state drain current	I _{D(ON)}	V _{GS} =-10V, V _{DS} =-5V	-60			A
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-10A		21		S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =-15V, f=1MHz		2060	2600	pF
Output Capacitance	C _{oss}			370		
Reverse Transfer Capacitance	C _{rss}			295		
Gate resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1MHz		2.4	3.6	Ω
Total Gate Charge	Q _g	V _{GS} =-10V, V _{DS} =-15V, I _D =-12A		30	39	nC
Gate Source Charge	Q _{gs}			4.6		
Gate Drain Charge	Q _{gd}			10		
Turn-On DelayTime	t _{d(on)}	V _{GS} =-10V, V _{DS} =-15V, R _L =1.25Ω, R _{GEN} =3Ω		11		ns
Turn-On Rise Time	t _r			9.4		
Turn-Off DelayTime	t _{d(off)}			24		
Turn-Off Fall Time	t _f			12		
Body Diode Reverse Recovery Time	t _{rr}	I _F =-12A, di/dt=100A/us		30	40	nC
Body Diode Reverse Recovery Charge	Q _{rr}			22		
Maximum Body-Diode Continuous Current	I _S				-3	A
Diode Forward Voltage	V _{SD}	I _S =-1A, V _{GS} =0V			-1	V

Note : The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

■ Marking

Marking	4407A KC****
---------	-----------------

P-Channel MOSFET AO4407A (KO4407A)

■ Typical Characteristics




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

P-Channel MOSFET AO4407A (KO4407A)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note E)