


Small Surface Mount Fast Recovery Rectifiers

RS207FL

■ Features

- For surface mounted applications
- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High temperature soldering :
260°C/ 10 seconds at terminals



■ Absolute Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified

Single phase half wave 60 HZ, resistive or inductive load For capacitive load, derate current by 20%

Parameter	Symbol	Value	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	
Maximum DC Blocking Voltage	V_{DC}	1000	
Maximum Instantaneous Forward Voltage (at $I_F=2A$)	V_F	1.3	A
Maximum Averaged Forward Rectified Current	I_{FAV}	2.0	
Peak forward surge current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	60	
Maximum DC Reverse Current Ta=25°C at rated DC blocking voltage	I_R	5 50	μA
Reverse Recovery Time	t_{rr}	500	
Typical Junction Capacitance	C_j	9	pF
Typical thermal resistance	R_{thJA}	180	°C/W
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55 to 150	

* 1 Reverse recovery condition $I_F = 0.5 A$, $I_R = 1 A$, $I_{rr} = 0.25 A$






* 2 Measured at 1MHz and applied reverse voltage of 4V D.C

* 3 Thermal resistance from junction to ambient.

Small Surface Mount Fast Recovery Rectifiers

RS207FL

■ Typical Characteristics




Small Surface Mount Fast Recovery Rectifiers

RS207FL

■ Package Outline Dimensions

Plastic surface mounted package; 2 leads

SOD-123FL



■ The recommended mounting pad size

